


CTF Silence Foam Floor Underlayment

CTF Silence Foam is a basic underlayment manufactured by using a close-cell polyethylene (or polypropylene) microcellular foam, it is a high-performance acoustic underlayment and moisture barrier used in residential and commercial flooring applications.

Hot Products



Plain IXPE underlay



Embossed IXPE underlay



Supreme IXPP underlay



Punched IXPE underlay

Dimensions

Item	Size in roll
1) Plain IXPE	- Density : 33 kg/m ³ , Thickness: 2 mm, 3 mm
2) Embossed IXPE	- Density 65 kg/m ³ , Thickness: 1.0 mm, 1.5 mm, 2 mm
3) Punched IXPE	- Density: 100kg/m ³ , Thickness: 1.5 mm, 2 mm
4) Supreme IXPP	- Width: 1.0 m, 1.1 m, or as request - Length: 200~300 m, or as request - Normal colors: gray and black
5) Damping mat	- Density: 33kg/m ³ , Thickness: 5mm, black

- For use under: all laminated, all engineered, all wood flooring
- For installation on: all types of sub-flooring, concrete



Damping pad

• Note: CTF produces more types of underlays by coating aluminum foil, pe film, etc. Welcome to inquire more details.




Impact Insulation




Sound Transmission



100% Environment Friendly



100% Mold & Mildew Resistant



100% Vapor Barrier

Sound & Impact Properties

(Sample tested: 65kg/m³, 5mm IXPE underlay)

IIC Classification: ASTM E989-18, 64 dB / STC Classification: ASTM E413-16, 51 dB